








P/N: LI-THEA-FL200

Note:

LI = Brand Code THEA = Product Series FL = Product Name, LED FLOOD LIGHT 200 = Power,200W



ADVANTAGE

- > CE ROHS Certificate.
- > IP67 driver, Input voltage 100-277VAC.
- > No UV or IR in the beam.
- Easy to install and Operate.
- Energy saving, Long lifespan.
- Light is soft and Uniform, Safe to eyes.
- Instant start, NO flickering, NO humming.
- > Green and eco-friendly without mercury.

APPLICATION

- Swimming Pool, Tennis Court;
- > Airfield, Dock Field;
- Large Square hall;
- > Highway Toll, Station etc.

















SPECIFICATIONS

| OPTICAL | Input Power | 200W | |
|------------|-----------------------|--|--|
| | Lumen | 23500LM | |
| | Lumen Efficacy | 117LM/W | |
| | Viewing Angle | 30° 60° 90° 140*70° 70*150° 150*80° 50*140° optional | |
| | Color Temperature | 3000K,4000K,5000K, 5700K,6500K | |
| | CRI | >70RA | |
| ELECTRICAL | Input Voltage | 100-277VAC 50/60Hz | |
| | PF | ≥0.95 | |
| | THD | ≤15% | |
| | Driver Model | Meanwell (0-10V/Dali Dimming Optional) | |
| | Optional Accessory | Motion Sensor/Surge-Protective Device | |
| MATERIALS | LED Type | SMD 3030 (1W) | |
| | LED QTY | 240 PCS | |
| | Housing | Aluminum Alloy | |
| | Housing Color | Any colors | |
| | Cover | Clear PC Lens | |
| | Waterproof Rating | Outdoor (IP66) | |
| OTHERS | Operating Temperature | -40℃ TO 50℃ | |
| | Operating Humidity | 10%-90% RH | |
| | Storage Temperature | -40℃ TO 80℃ | |
| | Storage Humidity | 10%-95% RH | |
| | Warranty Time | 5 Years | |

PACKAGE

| | Size | Qty / Carton | Lamps Net Weight | Weight/ Carton |
|------------|------------|--------------|------------------|----------------|
| Carton box | 56*46*16cm | 1PC | 5.5KG | 6.5KG |

